



Klemmsan®

270800 KPR-SCE-12VAC/DC-1C

1 C/O PLC Relay

Input	Nominal Voltage (Un)	12VAC/DC
	Operating Voltage Range	(0.8 - 1.15) x Un
	Release Voltage	0.2 x Un
	Integrated RCZ Filter	—
Power Consumption	AC	<0.35VA
	DC	<0.35W
Contact Characteristic	Type	1 C/O (SPDT)
	Material	AgSnO2
	Coil Voltage	12VDC
	Coil Empedance	212x(1±10%)Ω
	Coil Consumption	170mW
	Operate Time	Maks. 10ms
	Release Time	Maks. 5ms
	Max. Ratings - AC	6A/250VAC;1500VA
	Max. Ratings - DC	6A/30VDC;180W
Mechanical Lifetime	NO	≥ 10 ⁷ operations
Electrical Lifetime Operations (UL approval, 85°C)	NO	3x10 ⁴ operations
	NC	1x10 ⁴ operations

Plug-In Bridge 2

Definition —

Order Number —

Quantity

Type —

Dekafix

Type DG 10/6T

Definition Terminals Lebel's for interface relays

Order Number 505 390

Packing Units 360

Avrupa standartlarına uygunluk belgesi - CE Certificate

UL Sertifikası - UL Certificate

Order Info

270800 1 C/0 PLC Relay