


## Cable glands Progress® EMC nickel-plated brass with antikink spring



### Short entry thread Pg

- One-piece sealing insert
- not overall length insulated

|                                    |                                                                                                                    |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>                 | <b>1080.11.52.100</b>                                                                                              |
| EAN:                               | 7611614196329                                                                                                      |
| Material                           | Nickel-plated brass                                                                                                |
| Antikink spring                    | Stainless steel A2                                                                                                 |
| Seal                               | TPE                                                                                                                |
| O-ring                             | NBR                                                                                                                |
| Operation temperature              | -40°C / +100°C                                                                                                     |
| Protection class                   | IP 68 (up to 10 bar) / IP 69                                                                                       |
| Properties                         | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread                       | Pg 11                                                                                                              |
| Clamping range without insert min. | 8.0 mm                                                                                                             |
| Clamping range without insert max. | 10.0 mm                                                                                                            |
| Wrench size                        | 18/21 mm                                                                                                           |
| Dimension H                        | 69 mm                                                                                                              |
| Thread length L                    | 6 mm                                                                                                               |
| Dispatch                           | 10                                                                                                                 |

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

### Available on request:

- Long entry thread