


## Cable glands Progress® EMC Rapid nickel-plated brass with contact disc

**Short entry thread Pg****Type approval: Progress MS EMV Rapid**

- One-piece sealing insert
- not overall length insulated

|                       |                                                                                               |
|-----------------------|-----------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>1081.07.075</b>                                                                            |
| EAN:                  | 7611614207117                                                                                 |
| Material              | Nickel-plated brass                                                                           |
| Contact sleeve        | Nickel-plated brass                                                                           |
| Contact disc          | Stainless steel A2                                                                            |
| Seal                  | TPE                                                                                           |
| O-ring                | NBR                                                                                           |
| Operation temperature | -40°C / +100°C                                                                                |
| Protection class      | IP 68 (up to 10 bar) / IP 69                                                                  |
| NEMA Type rating      | 4X                                                                                            |
| Properties            | For a quick installation of partially dismantled cables as well as thoroughly shielded cables |
| Entry thread          | Pg 7                                                                                          |
| Clamping range min.   | 6.0 mm                                                                                        |
| Clamping range max.   | 7.5 mm                                                                                        |
| Wrench size           | 15 mm                                                                                         |
| Dimension H           | 20 mm                                                                                         |
| Thread length L       | 6 mm                                                                                          |
| Dispatch              | 50                                                                                            |