

## Synthetic cable glands Progress® GFK



### Entry thread metric

#### Type approval: Progress GFK

- Dark grey RAL 7001
- Two-piece sealing insert

|                                    |                                                                          |
|------------------------------------|--------------------------------------------------------------------------|
| <b>Article no:</b>                 | <b>1572.17</b>                                                           |
| E-No:                              | 121713408                                                                |
| EAN:                               | 7611614136783                                                            |
| Material                           | Agromid glass fiber reinforced, heat aging and impact-resistant modified |
| Properties                         | halogen-free                                                             |
| Seal                               | TPE                                                                      |
| Operation temperature              | -30°C / +100°C                                                           |
| Strain relief                      | Version A acc. to EN 62444                                               |
| Protection class                   | IP 68                                                                    |
| Entry thread                       | M16x1.5                                                                  |
| Clamping range with insert min.    | 6.0 mm                                                                   |
| Clamping range with insert max.    | 8.0 mm                                                                   |
| Clamping range without insert min. | 8.0 mm                                                                   |
| Clamping range without insert max. | 10.5 mm                                                                  |
| Wrench size                        | 21 mm                                                                    |
| Dimension H                        | 26.0 mm                                                                  |
| Thread length L                    | 12 mm                                                                    |
| Dispatch                           | 50                                                                       |