


# AGRO cable glands Progress® EMC Rapid nickel-plated brass with contact dis



## Short entry thread metric

### Type approval: Progress MS EMC Rapid EX

- One-piece sealing insert
- not overall length insulated

|                       |                                                                                               |
|-----------------------|-----------------------------------------------------------------------------------------------|
| <b>Article no:</b>    | <b>EX1081.20.110</b>                                                                          |
| EAN:                  | 7611614211763                                                                                 |
| Material              | Nickel-plated brass                                                                           |
| Seal                  | TPE                                                                                           |
| O-ring                | FPM                                                                                           |
| Operation temperature | -60°C / +100°C                                                                                |
| Protection class      | IP 66 / IP 68 (up to 10 bar)                                                                  |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31                                             |
| Gas                   | II 2G Ex eb IIC Gb                                                                            |
| Dust                  | II 2D Ex tb IIC Db                                                                            |
| Zone                  | Gas 1 and 2 / dust 21 and 22                                                                  |
| Certificate           | SEV 15 ATEX 0152X                                                                             |
| IECEx Certificate     | IECEx SEV 15.0019X                                                                            |
| CCC Certificate       | CCC 2022322313004811                                                                          |
| Properties            | For a quick installation of partially dismantled cables as well as thoroughly shielded cables |
| Entry thread          | M20x1.5                                                                                       |
| Clamping range min.   | 8.0 mm                                                                                        |
| Clamping range max.   | 11.0 mm                                                                                       |
| Wrench size           | 24 mm                                                                                         |
| Dimension H           | 25 mm                                                                                         |
| Thread length L       | 6 mm                                                                                          |
| Dispatch              | 50                                                                                            |

Long entry thread available on request