

# AGRO cable glands Ex Compact nickel-plated brass flameproof enclosure Ex



## Entry thread metric

### Type approval: EX Compact MS

- One-piece sealing insert
- not overall length insulated

|                       |                                                                    |
|-----------------------|--------------------------------------------------------------------|
| <b>Article no:</b>    | <b>EX1126.25.150</b>                                               |
| E-No:                 | 121442778                                                          |
| EAN:                  | 7611614242309                                                      |
| Material              | Nickel-plated brass                                                |
| Seal                  | NBR                                                                |
| O-ring                | FPM                                                                |
| Operation temperature | -60°C / +105°C                                                     |
| Protection class      | IP 66 / IP 68 (30 bar)                                             |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-1 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                   | II 2G Ex db eb IIC Gb                                              |
| Dust                  | II 2D Ex ta IIIC Da                                                |
| Zone                  | Gas 1 and 2 / dust 21 and 22                                       |
| Certificate           | PTB 10 ATEX 1034X                                                  |
| IECEx Certificate     | IECEx PTB 12.0055X                                                 |
| Entry thread          | M25x1.5                                                            |
| Clamping range min.   | 7.5 mm                                                             |
| Clamping range max.   | 15.0 mm                                                            |
| Wrench size           | 32 mm                                                              |
| Dimension H           | 28 mm                                                              |
| Thread length L       | 12 mm                                                              |
| Dispatch              | 20                                                                 |

### Available on request:

- Stainless steel A2 or A4