

## AGRO cable glands Progress® nickel-plated brass increased safety Ex e II for



### Short entry thread Pg

#### Type approval: Progress MS Multi EX

- One-piece sealing insert
- not overall length insulated

<b>Article no:</b>	<b>EX1310.09.4.015</b>
EAN:	7611614239385
Material	Nickel-plated brass
Seal	TPE / NBR
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0152X
IECEX Certificate	IECEX SEV 15.0019X
CCC Certificate	CCC 2022322313004811
Entry thread	Pg 9
Clamping range min.	1.0 mm
Clamping range max.	1.5 mm
Number of cables	4
Wrench size	18 mm
Dimension H	20 mm
Dimension L	6 mm
Note	3
Dispatch	50

3 = Material sealing insert NBR  
Suitable locking pins see accessories

#### Available on request:

- Executions in steel A2 and A4, entry thread NPT