


## AGRO cable glands Progress® nickel-plated brass increased safety Ex e II for



### Short entry thread metric

#### Type approval: Progress MS Multi EX

- One-piece sealing insert
- not overall length insulated

<b>Article no:</b>	<b>EX1310.32.6.070</b>
EAN:	7611614239330
Material	Nickel-plated brass
Seal	TPE / NBR
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0152X
IECEx Certificate	IECEx SEV 15.0019X
CCC Certificate	CCC 2022322313004811
Entry thread	M32x1.5
Clamping range min.	6.0 mm
Clamping range max.	7.0 mm
Number of cables	6
Wrench size	36 mm
Dimension H	28 mm
Dimension L	8 mm
Dispatch	25

3 = Material sealing insert NBR  
 Suitable locking pins see accessories

#### Available on request:

- Executions in steel A2 and A4, entry thread NPT