


AGRO cable glands Progress® nickel-plated brass increased safety Ex e II for



Short entry thread metric

Type approval: Progress MS Multi EX

- One-piece sealing insert
- not overall length insulated

| | |
|-----------------------|---|
| Article no: | EX1310.40.7.090 |
| EAN: | 7611614239354 |
| Material | Nickel-plated brass |
| Seal | TPE / NBR |
| O-ring | FPM |
| Operation temperature | -60°C / +100°C |
| Protection class | IP 66 / IP 68 |
| Test standard | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas | II 2G Ex eb IIC Gb |
| Dust | II 2D Ex tb IIIC Db |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | SEV 15 ATEX 0152X |
| IECEx Certificate | IECEx SEV 15.0019X |
| CCC Certificate | CCC 2022322313004811 |
| Entry thread | M40x1.5 |
| Clamping range min. | 8.0 mm |
| Clamping range max. | 9.0 mm |
| Number of cables | 7 |
| Wrench size | 46 mm |
| Dimension H | 31 mm |
| Dimension L | 8 mm |
| Note | 3 |
| Dispatch | 10 |

3 = Material sealing insert NBR
Suitable locking pins see accessories

Available on request:

- Executions in steel A2 and A4, entry thread NPT