

## AGRO synthetic cable glands Progress® GFK increased safety Ex e II and intri

**Entry thread Pg****Type approval: Progress GFK EX**

- Black / light blue RAL 5012
- One-piece sealing insert

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| <b>Article no:</b>    | <b>EX1530.48.490</b>                              |
| EAN:                  | 7611614179797                                     |
| Material              | Polyamide glass fiber reinforced                  |
| Properties            | halogen-free                                      |
| Seal                  | TPE / NBR                                         |
| Operation temperature | -20°C / +85°C                                     |
| Protection class      | IP 66 / IP 68                                     |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                   | II 2G Ex eb IIC Gb                                |
| Dust                  | II 2D Ex tb IIIC Db                               |
| Intrinsic safety gas  | II 2G Ex ia IIC Ga                                |
| Intrinsic safety dust | II 2D Ex ia IIIC Da                               |
| Zone                  | Gas 0, 1 and 2 / dust 20, 21 and 22               |
| Certificate           | SEV 15 ATEX 0152X                                 |
| IECEx Certificate     | IECEx SEV 15.0019X                                |
| CCC Certificate       | CCC 2022322313004811                              |
| Entry thread          | Pg 48                                             |
| Clamping range min.   | 47.0 mm                                           |
| Clamping range max.   | 49.0 mm                                           |
| Wrench size           | 70 mm                                             |
| Dimension H           | 46 mm                                             |
| Thread length L       | 16 mm                                             |
| Dispatch              | 5                                                 |

3 = Material sealing insert NBR

**Available on request:**

- For installation of multiple cables