

Product datasheet:

Reduction fittings nickel-plated brass increased safety Ex e II

Outer thread metric or Pg

Approval type: Reduktion MS EX

- Outer thread Pg
- Inner thread metric
- with O-ring
- 1 = Metric coarse-pitch thread (with VDE Testreport)
- 2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X
- The norm interdicts to screw several reduction/enlarging fittings into each other!



Article no.:  **EX3500.21.17**

E-No: 000000000

EAN: 7611614175966

Delivery: 25

Dimensions / Form

Product length: 7.5 mm


Spanner size: 30 mm

External thread: Pg 21

Internal thread: M16x1.5

Dimension H: 3.5 mm

Dimension L: 7.5 mm



Connections / Entries

clamp technology: Compression technology

Features

Product type: reduction

Approvals / Certifications

Protection class: IP66

Explosion-proof design: Yes

EX zone: Gas 1 and 2 - Dust 21 and 22

Gas: II 2G Ex eb IIC Gb

Dust: II 2D Ex tb IIIC Db

Test standard: IEC EN 60079-7

IECEx certification: IECEx SEV 15.0018

Further certifications: SEV 15 ATEX 0151

Connectivity certification: SEV 15 ATEX 0151



Storage / Installation / Operation

Minimum operating temperature: -60 °C

Product datasheet:

Maximum operating temperature: _____ 100 °C