Product datasheet:

Reduction fittings nickel-plated brass increased safety Ex e II

Outer thread metric or Pg

Approval type: Reduktion MS EX

· Outer thread Pg
· Inner thread metric
· with O-ring
· 1 = Metric coarse-pitch thread (with VDE Testreport)
· 2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X
· The norm interdicts to screw several reduction/enlarging fittings into each other!

Article no.:	**EX3500.42.32**
E-No:	000000000
EAN:	7611614176062
Delivery:	10



Dimensions / Form

Product length:	10 mm
Spanner size:	55 mm
External thread:	Pg 42
Internal thread:	M32x1.5
Dimension H:	5.0 mm
Dimension L:	10 mm

Connections / Entries

clamp technology:	Compression technology

Features

Product type:	reduction

Approvals / Certifications

Protection class:	IP66
Explosion-proof design:	Yes
EX zone:	Gas 1 and 2 - Dust 21 and 22
Gas:	II 2G Ex eb IIC Gb
Dust:	II 2D Ex tb IIIC Db
Test standard:	IEC EN 60079-7
IECEx certification:	IECEx SEV 15.0018
Further certifications:	SEV 15 ATEX 0151
Connectivity certification:	SEV 15 ATEX 0151

Storage / Installation / Operation

Minimum operating temperature:	-60 °C

Product datasheet:

Maximum operating temperature:	100 °C