

Product datasheet:

Enlarging fittings nickel-plated brass increased safety Ex e II

Outer thread metric or Pg

Approval type: Erweiterung MS EX

- Outer thread Pg
- Inner thread metric
- with O-ring
- 2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X
- The norm interdicts to screw several reduction/enlarging fittings into each other!



Article no.: **EX3600.29.50**

E-No: 000000000

EAN: 7611614175171

Delivery: 10

Dimensions / Form

Product length: 8 mm


Spanner size: 55 mm

External thread: Pg 29

Internal thread: M50x1.5

Dimension H: 16.0 mm

Dimension L: 8 mm



Connections / Entries

clamp technology: Compression technology

Features

Product type: expansion



Approvals / Certifications

Protection class: IP66

Explosion-proof design: Yes

EX zone: Gas 1 and 2 - Dust 21 and 22

Gas: II 2G Ex eb IIC Gb

Dust: II 2D Ex tb IIIC Db

Test standard: IEC EN 60079-7

IECEx certification: IECEx SEV 15.0018

Further certifications: SEV 15 ATEX 0151

Connectivity certification: SEV 15 ATEX 0151

Storage / Installation / Operation

Minimum operating temperature: -60 °C

Product datasheet:

Maximum operating temperature: _____ 100 °C