



**Klemsan**®





**KKD 6080**



Order		
RAL 7030 - Stone Grey	Thin Slot (4-6)	555 6080

Dimensions	
Length	2.000,00 mm
Width	60,00 mm
Height w/o cover	76,80 mm
Height w/ cover	80,00 mm

Technical Data			
Material	PVC	Package Qty.	12 pcs. x 2 mt.
Inflammability	UL 94 V0	Wire Fill Capacity	60%
Max. Service Temp.	60°C	Min. Service Temp.	-15°C
Max. Operating Temp.	60°C	Min. Operating Temp.	-5°C

Certifications	
<b>Certificate</b>	<b>Standard</b>
CE	EN 50085-2-3
TSE	TS EN 50085-2-3
EAC	GOST R 53313:2009
cULus	UL 1565-C22.2No.18.5-02

Accessories				
Description	Type	Colour	Cat. No.	Qty.
Duct Cutter (Scissor)	KKMR		553230	1
Duct Cutter	KMK 1002		553220	1
Cable Duct Cover	KDK 60	RAL 7030	551052	10 pcs. x 2 mt.
Rivet Setting Tool	SETR	Black	553500	1
Plastic Rivet 6,5 mm	PPE 6,5	Grey	553600	100
Cable Clamp	KKB	Black	553405	10
Wire Retainer	KKT 6080	Black	553335	10
Cable Holder	KKM	Black	553415	10